

Kent Cams Megadyne Nockenwellen

Art.-Nr.	St. Zeiten		Dauer(*)		Volle Öffn. (*)	Ventilhub(*)		Ventilspiel	Ventil-Federn	Stößelbecher
	Einlaß	Auslaß	Einlaß	Auslaß		1:1,25	1:1,5			
KC MD 256	21/53	53/21	254	254	106	.320/.320	.380/.380	.016"	VS2 (1000cc) VS4 (1275cc)	C-AEG 579
KC MD 266	24/56	61/29	260	268	106	.320/.320	.380/.390	.016"	VS2 (1000cc) VS4 (1275cc)	C-AEG 579
KC MD 266i					110	-/-	-/-	0.16"	Serienfedern	C-AEG 579
KC MD 276	29/61	66/34	270	280	106	.360/.380	.430/.455	.016"	VS2 (1000cc) VS4 (1275cc)	C-AEG 579
KC MD 286	34/66	71/39	280	290	106	.388/.400	.460/.468	.016"	VS4 (in 1275cc SS8 verwenden)	C-AEG 579R
KC MD 296	39/71	76/44	290	300	106	.400/.420	.470/.495	.016"	VS39	C-AEG 579R
KC MD 310	49/81	81/49	310	310	106	.420/.420	.495/.495	.016"	VS39	C-AEG 579R

